

## **mmsv2** (version 0.4, 23 mar 2008)

### **Classes**

Player  
PlayList

#### **class Player()**

**Player**(player)

player : bool (use player to play video (True) or audio (False))

**Default values:**

player=False

**Methods defined here:**

**play**() -- Starts playing current media file from internal playlist.

**play**(path, [title])

path : string  
title : string

Method will clear internal playlist and add given media file to internal playlist. It will then start to play media file.

**play**(position)

position : integer

Starts playing media file in given position from internal playlist.

**play**(playlist)

playlist : PlayList (see class below)

Method will clear internal playlist and add media files from given playlist. It will then start to play first media file in internal playlist.

**stop**() -- Stop player.

**pause**() -- Pause player.

**mute**() -- Mute player.

**volup**() -- Increase volume.

**voldown**() -- Decrease volume.

**ff**() -- Fast forward.

```
fb() -- Fast backward.  
next() -- Play next in internal playlist.  
prev() -- Play previous in internal playlist.  
getPlaylist() -- Get a reference to internal playlist.
```

## class **PlayList()**

```
PlayList()
```

Methods defined here:

```
load(path)
```

```
path          : string
```

Method will load a file from disk. Format of the file can be mms playlists or shoutcast like playlists.

```
clear() -- Will remove all media files from the playlist.
```

```
remove(position)
```

```
position      : integer
```

Method will remove media file in given position from playlist.

```
add(path, [title])
```

```
path          : string  
title         : string
```

Method will add given media file to playlist.

```
toList() -- Returns a list containing all playlist titles.
```

```
size()-- Returns number of media files in playlist.
```

## Author

Fredrik